

## TECHNICAL DATA SHEET



# SYNTHETIC SAE 0W-30 RACING ONLY

PRODUCT # 10605, 10606, 10607,  
10608, 10609

### TEST

### ASTM

### TYPICAL

API Gravity	D-1298	33.2
Specific Gravity @ 60°F	D-1298	0.859
Density @ 60°F LBS/US Gal	D-1298	7.16
Viscosity @ 40°C, cSt	D-445	63.6
Viscosity @ 100°C, cSt	D-445	11.3
Flash Point COC °F	D-92	445
Color		Amber
Viscosity Index	D-2270	168
CCS @ -35°C, CPS	D-5293	6,200 Max
MRV @ -40°C, CPS	D-4684	60,000 Max
Zinc, Wt %	X-Ray	3000 PPM Typical

Lucas Synthetic SAE 0W-30 Racing Oil is made with the highest quality synthetic base oils and is fortified with a unique additive package containing high levels of zinc, molybdenum and phosphorus, which provides a tougher, thicker additive film for maximum protection even under the most severe conditions. It lowers oil temperatures, extends oil life and minimizes metal fatigue. It has excellent cold temperature properties and stands up to high operating temperatures.

Lucas Synthetic SAE 0W-30 Racing Oil is typically used in NASCAR, Late Model, Super Late Model, ARCA, Modifieds, Sprint Cars, Midgets, IRL, NHRA, Stock, Super Stock, Comp and Super Comp. Excellent for use with turbo charged engines.

Lucas Synthetic SAE 0W-30 is for RACING APPLICATIONS ONLY. It is not recommended for passenger car use.